





































12W-30W G120 COB LED til erstatning for 35W-120W Metalhalogen lyskilder.



Specification of COB G12 LED 12W 1000LM CRI 92

	Voltage	85-265V		Wattage	12W
	Equivalent	35W Metal halide G12		Lumens	900-1000Lms
	Color Range	Warm/Natural/Cool white		Color Temperature	3000k, 4000K,6000k
	Base	G12		Beam Angle	24°,38°,60°
	Dimmable	YES		Working Temperature	-40- +60°C
	IP Rated	IP44		Material	Aluminum
	Diameter	50mm		Length	100mm
	Weight	0.3KG		Lifespan	50,000Hrs
	Certificate	CE RoHS		Warranty	3 Years

Specification of COB G12 LED 20W 1900LM CRI 92

	Voltage	85-265V		Wattage	20W
	Equivalent	70W Metal halide G12		Lumens	1600-1900Lms
	Color Range	Warm/Natural/Cool white		Color Temperature	3000k, 4000K,6000k
	Base	G12		Beam Angle	24°,38°,60°
	Dimmable	YES		Working Temperature	-40- +60°C
	IP Rated	IP44		Material	Aluminum
	Diameter	50mm		Length	100mm
	Weight	0.3KG		Lifespan	50,000Hrs
	Certificate	CE RoHs		Warranty	3 Years

NB!

12W versionen er med indbygget driver og kræver blot bypass af eksisterende ballast - 20W og op er med ekstern driver og kræver udskiftning af eksisterende ballast til den medfølgende driver.